



PiXORD PL721S is a professional bullet camera offering 1080p Full HD resolution with superb image quality up to 30 fps. Featuring 2MP Full HD resolution and high-performance H.264/MPEG-4/MJPEG compression technology, the PL721S offers extra-smooth video and wide coverage. PL721S employs many advanced features to allow users to fully utilize the high definition video. By adopting the advanced image sensor, the low-light performance has been further gained. PL721S is therefore ideal for the application of critical lighting condition. It is even capable to deliver color images in the scene of darkness.


Aimed at outdoor surveillance, PL721S is furnished with an auto-iris lens, a removable IR-cut filter, 15-meter IR illuminators, Wide Dynamic Range (WDR), and multi-functional environment profile image settings for superior image quality around the clock. Moreover, the IP67-rated housing protects against rain and dust and ensures functional operation in all types of weather conditions.

With other advanced features such as tamper detection, 802.3af compliant PoE, ONVIF Compliant for interoperability, built-in SD/SDHC/SDXC card slot for storage, two-way audio, and digital input / output for alarm, the PL721 is an all-in-one bullet network camera for detailed surveillance in outdoor environments.

## Features

- 2-Megapixel CMOS Sensor
- 30 fps@1080p Full HD
- *PL721SE* : 3-10 mm Vari-focal , DC-iris Lens ; *PL721SF* : 6 mm Fixed-focal, Fixes-iris Lens
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 15 Meters
- Real-time H.264, MPEG-4, and MJPEG Compression
- Low Lux for Night Vision
- WDR Enhancement for Visibility in Extremely Bright or Dark Environments
- Two-way Audio Communication
- Built-in MicroSD Card Slot, support SDHC/SDXC 64GB or above
- Weather-proof IP67-rated Housing
- Built-in 802.3af Compliant PoE
- ONVIF Compliant for interoperability



System Information		Interface	10 Base-T/100 BaseTX Ethernet(RJ-45)
CPU	Multimedia SoC (System-on-Chip)	ONVIF	Ver. 2.2
NOR Flash	16MB	Intelligent Video	
RAM	512 MB	Motion Detection	Ten-window video motion detection
Camera Features		Alarm and Event	
Image Sensor	1/2.8" Progressive CMOS sensor	Alarm Triggers	Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification
Maximum Resolution	1920x1080	Alarm Events	Event notification using digital output, HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server
Lens Type	PL721E: Vari-focal ( Ø 14 mm) PL721F: Fixed-focal ( M12*0.5)	General	
Focal Length	PL721E: f = 3-10 mm PL721F: f = 6 mm	Connectors	DC 12V Power input RJ-45 connector for Network/PoE connection RJ-45 connector for Multi-function <ul style="list-style-type: none"> <li>• Audio input</li> <li>• Audio output</li> <li>• Digital input x1</li> <li>• Digital output x1</li> </ul>
Aperture	PL721E: F1.2~2.2, DC-iris PL721F: F1.2, Fixed-iris		
Field of View	PL721E: 31.7°~96.4°(H); 23.7°~69.6°(V); 39.7°~128.2°(D) PL721F: 48.8°(H)/ 36.6°(V)/ 61°(D)		
Shutter Time	1 sec. to 1/1,000,000 sec.		
WDR Technology	WDR Enhanced	LED Indicator	System power and status indicator
Day/Night	Removable IR-cut filter for day & night function	Power Input	DC 12V IEEE 802.3af PoE
Minimum Illumination	0.005 Lux @F1.2 (Color) ; 0 Lux@F1.2 (IR On)	Power Consumption	IR ON Max. 12W (DC 12V / PoE) IR OFF Max. 5W (DC 12V / PoE)
IR Illuminators	Built-in IR illuminators, effective up to 15 meters High Power IR LED x8	Dimensions	Ø:200 L x 82H x 82W mm
On-board Storage	Built-in MicroSD card slot, support SDHC/SDXC 64GB or above	Weight	Net: 350g
Video		Casing	Weather-proof IP67-rated housing
Compression	H.264, MJPEG & MPEG-4	Safety Certifications	CE, FCC Class B, LVD
Maximum Frame Rate	30 fps at all resolutions; Stream1: 1920x1080@30fps Stream2: 1280x720@30fps Stream3: 640x360@30fps	Operating Temperature	0°C ~ 50°C
Maximum Streams	3 simultaneous streams	Operating Humidity	10% ~ 80%
S/N Ratio	Above 50 dB	System Requirements	
Dynamic Range	Above 70dB	Operating System	Microsoft Windows 7/Vista/XP/2000
Video Streaming	Adjustable resolution, quality and bitrate ROI (Region of Interest) for Enhancement of Image Quality	Web Browser	Mozilla Firefox 7 ~ 10, Internet Explorer 7.x or 8.x, Chrome / Safari 4.0 or above
Image Settings	Adjustable image size, quality and bitrate Configurable brightness, saturation, exposure control, sharpness, contrast, white balance, auto shutter control, auto gain control, noise reduction, EV luminance control, flip & mirror, privacy masks, time stamp, text overlay	Other Players	VLC: 1.1.11 or above
Audio		Included Accessories	
Audio Capability	Audio input/output (full duplex); RJ45 port	Quick installation guide, screws pack, I/O cable, mounting bracket, software CD	
Compression	G.711u	Dimensions	
Interface	External microphone input		
Network			
Users	Live viewing for up to 10 clients		
Protocols	HTTP,HTTPS, TCP/ IP,IPv4, UDP, SMTP, FTP, DHCP, DDNS, NTP, DNS, ARP,RTSP, RTP, UPnP, ONVIF(Profile S),Multicast		